

09/689615

CofC



PATENT
Customer No. 22,852
Attorney Docket No. 04350.0012-00000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re U.S. Patent No.: 6,953,127)
Inventors: Richard A. ESSER et al.)
Issue Date.: October 11, 2005)
For: RAPID DEPLOY HAZMAT)
CONTAINMENT DEVICE)

Certificate
FEB 08 2006
of Correction

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

RENEWED REQUEST FOR CERTIFICATE OF CORRECTION

Pursuant to 35 U.S.C. § 254, and 37 C.F.R. § 1.322, this is a renewed request for a Certificate of Correction in the above-identified patent. As stated in the Request for Certificate of Correction filed in the U.S. Patent and Trademark Office ("PTO") on December 12, 2005, the mistakes identified in the appended PTO Form 1050 occurred through the fault of the Patent Office. Recently, however, Applicants received a January 5, 2006 Notice from the PTO denying Applicants' request. A copy of the January 5th Notice is enclosed for reference purposes.

Applicants filed a Petition to Correct Inventorship on July 16, 2003, requesting that Mr. Chad Sample be added as an inventor in the then pending application. In response, the PTO accepted the inventorship correction in an August 19, 2005 Decision Granting Petition. Issued U.S. Patent No. 6,953,127 does not, however, identify Mr. Sample as a named inventor. The enclosed January 5th Notice does not address this

FEB 13 2006

error nor does the Notice mention any decision by the PTO's to correct it. Copies of the as filed Petition and the PTO's Decision Granting Petition are enclosed for reference purposes.

In addition, Applicants included a complete and accurate claim listing in an Appendix of the Supplemental Appeal Brief filed on March 1, 2004. The listing included all of the claims pending in this case as of March 1, 2004. The version of claim 1 listed in the as filed Appendix recites, among other things, a rapid deploy containment device comprising rods, hubs, each end portion being rotatable about its axis of revolution, and a canopy connected to at least two hubs. The version of claim 1 recited in U.S. Patent No. 6,953,127 (both at page 1 and at column 6, lines 17-41) does not, however, match the version of claim 1 listed in the as filed Appendix. Thus, contrary to statement in the PTO's January 5th Notice, claim 1 of issued U.S. Patent No. 6,953,127 is not printed in accordance with the record. A copy of the as filed Appendix is enclosed for reference purposes.


Two (2) copies of PTO Form 1050 are also appended. The complete Certificate of Correction involves one (1) page. Issuance of the Certificate of Correction containing the corrections is once again earnestly requested. In addition, Applicants respectfully request that representatives from the Decisions & Certificates of Correction Branch contact the undersigned if any further information or clarification is needed. The undersigned can be reached by phone at 202.408.4187.

Please charge any required fees not included herewith to our deposit account
06-0916.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER, L.L.P.

Dated: February 3, 2006

By: 
Dominic P. Ciminello
Reg. No. 54,038

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. 6,953,127 B1
DATED: October 11, 2005
INVENTORS: Richard A. Esser et al.

It is hereby certified that errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On page 1, the names listed under the heading "Inventor" should read "Richard A. Esser, Glenn Dale, MD (US); Chad Sample, Glenn Dale, MD (US)"

Beginning at col. 6, line 17, Claim 1 should read:

"A rapid deploy containment device adapted to receive and retain hazardous waste, the containment device being convertible between an erect open configuration and a collapsed compact configuration, the containment device in the erect open configuration forming a receptacle region, the containment device comprising:

rods, each rod being pivotally joined to another rod by a scissors connection intermediate the ends of said rod;

hubs, each hub receiving an end portion of at least two rods along separate axes of each hub, the end portion being pivotally joined to said hub, where the end portion pivots in relation to said hub along a single axis of revolution, each end portion pivoting along separate axes of revolution in relation to said hub,

each end portion being rotatable about its axis of revolution from the collapsed compact configuration, where all of said rods are substantially parallel to one another, to the erect open configuration, the containment device articulating along three axes, whereby the containment device changes between the compact and open configurations in height, length and width; and

a canopy connected to at least two hubs and residing in the receptacle region of the erect open containment device."

MAILING ADDRESS OF SENDER

Finnegan, Henderson, Farabow,
Garrett & Dunner, L.L.P.
901 New York Avenue, N.W.
Washington, D.C. 20001-4413

Patent No. 6,953,127

No. of additional copies
@ .30¢ per page

0

FEB 13 2006

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. 6,953,127 B1
DATED: October 11, 2005
INVENTORS: Richard A. Esser et al.

It is hereby certified that errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On page 1, the names listed under the heading "Inventor" should read "Richard A. Esser, Glenn Dale, MD (US); Chad Sample, Glenn Dale, MD (US)"

Beginning at col. 6, line 17, Claim 1 should read:

"A rapid deploy containment device adapted to receive and retain hazardous waste, the containment device being convertible between an erect open configuration and a collapsed compact configuration, the containment device in the erect open configuration forming a receptacle region, the containment device comprising:

rods, each rod being pivotally joined to another rod by a scissors connection intermediate the ends of said rod;

hubs, each hub receiving an end portion of at least two rods along separate axes of each hub, the end portion being pivotally joined to said hub, where the end portion pivots in relation to said hub along a single axis of revolution, each end portion pivoting along separate axes of revolution in relation to said hub,

each end portion being rotatable about its axis of revolution from the collapsed compact configuration, where all of said rods are substantially parallel to one another, to the erect open configuration, the containment device articulating along three axes, whereby the containment device changes between the compact and open configurations in height, length and width; and

a canopy connected to at least two hubs and residing in the receptacle region of the erect open containment device."

MAILING ADDRESS OF SENDER

Finnegan, Henderson, Farabow,
Garrett & Dunner, L.L.P.
901 New York Avenue, N.W.
Washington, D.C. 20001-4413

Patent No. 6,953,127

No. of additional copies
@ .30¢ per page

0

FEB 13 2006



1/5/04

UNITED STATES DEPARTMENT OF COMMERCE
Patent and Trademark Office
ASSISTANT SECRETARY OF COMMERCE AND
COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, DC 20231

Patent No. : 6953127
Inventor(s) : Richard A. Esser et al.
Issued : 10/11/05
Title : IMPROVED CEILING HINGE ASSEMBLY
Atty.doc./File No.

Request for Certificates of Correction

Consideration has been given to your request for the issuance of a Certificate of Correction, for the above – identified patent under the provisions of CFR 1.322.

Inspection of the application for the patent reveals that on page 1 & col. 6 line 17 claim 1 is printed in accordance with the record. Therefore being no fault on the Patent and Trademark Office, It has no authority to issue a certificate of correction under the provision of 1.322.

In view of the forgoing, your request in this matter, is hereby denied.

Future written correspondence concerning this matter should be filed and directed to Decisions & Certificates of Correction Branch.

Henry Randall
Cecelia Newman
Decisions & Certificates
of Correction Branch
(703) 308-9390 Ext. 108

FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.
901 NEW YORK AVENUE, N.W.
WASHINGTON, DC 20001-4413

HR/CBN

RECEIVED

JAN 13 2006

FINNEGAN, HENDERSON, FARABOW,
GARRETT AND DUNNER, LLP

1/13/06
DL



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

hjm - phs DPC

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/689,615	10/13/2000	Richard A. Esser	04350.0012-00000	8050

22852 7590 08/19/2005

FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER
LLP
901 NEW YORK AVENUE, NW
WASHINGTON, DC 20001-4413

EXAMINER

CASTELLANO, STEPHEN J

ART UNIT

PAPER NUMBER

3727

DATE MAILED: 08/19/2005

RECEIVED

AUG 22 2005

FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER, LLP

Please find below and/or attached an Office communication concerning this application or proceeding.

Dh
8-22-05
B



UNITED STATES DEPARTMENT OF COMMERCE

U.S. Patent and Trademark Office

Address: COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

APPLICATION NO/ CONTROL NO.	FILING DATE	FIRST NAMED INVENTOR / PATENT IN REEXAMINATION	ATTORNEY DOCKET NO.
--------------------------------	-------------	---	---------------------

09/689-615

EXAMINER


ART UNIT	PAPER
----------	-------

81705

DATE MAILED:

Please find below and/or attached an Office communication concerning this application or proceeding.

Commissioner for Patents


Stephen J. Castellano
Primary Examiner
Art Unit: 3727



UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents
United States Patent and Trademark Office
P.O. Box 1450
Alexandria, VA 22313-1450
www.uspto.gov

In re ESSER, RICHARD A.
Appl No.: 09/689,615
Filed: October 13, 2000
For: Rapid Deploy Hazmat Containment Device

:
:
: **DECISION GRANTING**
: **PETITION**
: **37 CFR 1.48**
:
:
:
:
:

This is a decision on the petition filed July 16, 2003 to correct inventorship under 37 CFR 1.48.

The petition is granted.

The patented file is being forwarded to Technology Center 3700 for correction in the PALM database.

Stephen J. Castellano
Primary Examiner
Art Unit 3727
Technology Center 3700

FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER
LLP
901 NEW YORK AVENUE, NW
WASHINGTON, DC 20001-4413

APPENDIX - CLAIMS ON APPEAL

1. A rapid deploy containment device adapted to receive and retain hazardous waste, the containment device being convertible between an erect open configuration and a collapsed compact configuration, the containment device in the erect open configuration forming a receptacle region, the containment device comprising:

rods, each rod being pivotally joined to another rod by a scissors connection intermediate the ends of said rod;

hubs, each hub receiving an end portion of at least two rods along separate axes of each hub, the end portion being pivotally joined to said hub, where the end portion pivots in relation to said hub along a single axis of revolution, each end portion pivoting along separate axes of revolution in relation to said hub,

each end portion being rotatable about its axis of revolution from the collapsed compact configuration, where all of said rods are substantially parallel to one another, to the erect open configuration, the containment device articulating along three axes, whereby the containment device changes between the compact and open configurations in height, length and width; and

a canopy connected to at least two hubs and residing in the receptacle region of the erect open containment device.

2. The containment device recited in claim 1, wherein each of said hubs includes flanges, where at least two of the flanges receive the end portion of said rods.

3. The containment device recited in claim 2, wherein the end portion of each of said rods is pivotally jointed to one of said flanges by a pin inserted through the end portion of said rod and received on said flange.

4. The containment device recited in claim 2, wherein the at least two flanges lay substantially perpendicular to one another, whereby each of said hubs receives rods along a first axis and a second axis perpendicular to the first axis.

5. The containment device recited in claim 4, wherein the ends of said substantially perpendicular flanges bend at right angles in either a clockwise or counterclockwise direction.

6. The containment device recited in claim 5, wherein the end portion of each of said rods is pivotally joined to a hub by a pin inserted through the end portion of said rod and received on two opposing flanges.

7. The containment device recited in claim 1, wherein each of said hubs includes a base portion, the end portion of each of said rods being pivotally joined to said base portion by a pin inserted through the end portion of said rods and received on said base portion.

8. The containment device recited in claim 2, wherein said hub includes a base portion, where the at least two flanges project from said base portion.

9. The containment device recited in claim 1, wherein each rod is of substantially equal length and wherein said scissor connection is proximate the middle of each rod.

13. The containment device recited in claim 1, further comprising a liner positioned in the receptacle region adjacent said canopy, said liner being made of a material resistive to hazardous chemicals.

20. A rapid deploy containment device adapted to receive and retain hazardous waste, the containment device being convertible between an erect open configuration and a collapsed compact configuration, the containment device comprising:

rods, each rod being pivotally joined to another rod by a scissors connection intermediate the ends of said rod;

hubs, each hub receiving an end portion of at least two rods along separate axes of each hub, the end portion being pivotally joined to said hub, where the end portion pivots in relation to said hub along a single axis of revolution,

each end portion being rotatable about its axis of revolution from the collapsed compact configuration, where all of said rods are substantially parallel to one another and where said hubs are positioned adjacent one another at each end portion of the collapsed compact configuration, to the open erect configuration, wherein the hubs positioned proximate a top portion of the collapsed compact configuration descend downward toward a bottom portion of the containment device when converting from the

collapsed compact configuration to the erect open configuration and wherein the containment device articulates between the collapsed compact configuration and the erect open configuration in height, length, and width; and

a canopy affixed to at least two hubs proximate the top portion of the containment device in the open erect configuration to form the receptacle region capable of receiving and retaining hazardous chemicals.

21. The containment device recited in claim 1, wherein the canopy is made of a material resistive to hazardous chemicals.

29. A portable containment device comprising:

a frame movable between a closed configuration, in which the frame delimits a negligible area, and an open configuration, in which the frame forms a plurality of walls defining a central space, wherein the frame comprises:

a plurality of rods, each rod comprising a first end, a second end, and an intermediate portion, wherein the intermediate portion of each rod is pivotably connected to the intermediate portion of another rod;

a plurality of first hubs, each first hub receiving first ends of at least two respective rods, wherein each respective rod is pivotable with respect to the first hub about a distinct axis; and

a plurality of second hubs configured to engage a support surface, each second hub receiving second ends of at least two respective rods, wherein each respective rod is pivotable with respect to the second hub about a distinct axis; and

a receptacle comprising a plurality of attachment portions secured to respective first hubs, wherein the receptacle collapses when the frame is in the closed configuration and the receptacle forms a containment volume in the central space when the frame is in the open configuration.

30. The device of claim 29, wherein the frame defines a length, a width, and a height and wherein the length, the width, and the height of the frame in the closed configuration are different from the length, the width, and the height of the frame in the open configuration.

31. The device of claim 30, wherein the length and the width of the frame in the closed configuration are less than the length and the width of the frame in the open configuration.

32. The device of claim 30, wherein the height of the frame in the closed configuration is greater than the height of the frame in the open configuration.

33. The device of claim 29, wherein at least one rod received by a first hub is pivotable about a first axis and wherein at least one other rod received by the first hub is pivotable about a second axis substantially perpendicular to the first axis.



34. The device of claim 29, wherein at least one rod received by a second hub is pivotable about a third axis and wherein at least one other rod received by the second hub is pivotable about a fourth axis substantially perpendicular to the third axis.



PATENT
Customer No. 22,852
Attorney Docket No. 04350.0012-00000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
)
Richard A. ESSER) Group Art Unit: 3727
)
Application No.: 09/689,615) Examiner: Castellano, S.
)
Filed: October 13, 2000)
)
For: RAPID DEPLOY HAZMAT)
CONTAINMENT DEVICE)

Mail Stop Petitions

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

PETITION TO CORRECT INVENTORSHIP UNDER 37 C.F.R. § 1.48(a)

Applicant hereby petitions to amend inventorship pursuant to 37 C.F.R. § 1.48(a).

Applicant respectfully requests that the following named inventor be added to the instant application: Chad SAMPLE, as noted in the Declaration filed herewith. Mr. Sample's name was inadvertently omitted from the previously filed documents in the instant application without deceptive intention on his or Applicant's part.

In accordance with 37 C.F.R. § 1.48(a), the following are being filed herewith:

(1) a declaration from the person being added as an inventor that the error in inventorship occurred without deceptive intent on his part; (2) a declaration by the added inventor as required by 37 C.F.R. § 1.63; and (3) the \$130.00 fee set forth in 37 C.F.R. § 1.17(i).

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

If there are any other fees due in connection with the filing of this Petition, please charge the fees to our Deposit Account No. 06-0916.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER, L.L.P.

Dated: July 16, 2003

By: Christopher H. Kirkman
Christopher H. Kirkman
Reg. No. 46,223

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com